



Technical Data

| | |
|-------------------------|---|
| H/OFF : | 300°C ± 10°C |
| L/OFF : | 0°C |
| BREAKING CAPACITY | C-1 15(3)A 400 VAC C-2 2.5(0.6)A 400VAC |
| MAX °C AROUND THE BODY: | T110°C |
| MAX °C AROUND THE BULB: | UPPER SWITCHING VALUE +15% |
| LIFE OF PRODUCTS: | 100.000 CYCLES |
| DIFFERENTIAL: | 10°C ± 5°C |
| MINIMUM CURRENT: | 200 mA |
| INSULATION RESISTANCE: | > 100 M OHM |
| RIF: | 300C-556-12M |



DESCRIZIONE :
Termostato reg. 0/300°C SP-DT cap. mm 1500 inox faston 6.3 X 0.8

| | | | | | |
|-------------------------|------------|--------------|---------|------------|-------|
| SCALA : | 1 : 2 | DISEGNATO : | SALA A. | MODIFICA : | DATA: |
| DATA : | 12/05/2015 | CONTROLLATO: | | | |
| TOLL.GEN. : | +/-0,1 | | | | |
| Descrizione revisione : | | | | Data | |
| Descrizione revisione : | | | | Data | |
| Descrizione revisione : | | | | Data | |