

AR580

Temperature transmitter

APAR

- linear processing of measured temperature into a current or voltage signal
- universal input:
 - thermoresistance Pt100
 - termoparowe J, K, S, N, E
- output current 4÷20mA (2-wire with power supply in current loop) or voltage 0÷10V (3-wire)
- no galvanic separation input / output
- housing for mounting on TS35 strip (DIN rail)
- input type, processing range and other processing parameters configured with AR950, AR956 programmer or AR956 programming set or by the manufacturer according to customer specifications
- exceeded processing range or sensor error signalled with a LED
- high accuracy and immunity to interference

AR956 programmer can be used to power transmitter from computer's USB port during parameter configuration.



TECHNICAL DATA

Universal input (programmable)

	measuring range
- Pt100 (3- or 2-wire)	-100 ÷ 850 °C
- thermocouple J	-5 ÷ 800 °C
- thermocouple K	-5 ÷ 1200 °C
- thermocouple S	-5 ÷ 1600 °C
- thermocouple N	-5 ÷ 1300 °C
- thermocouple E	-5 ÷ 700 °C

Cold ends temperature compensation

Lead resistance for Pt100 Rd<25Weach line 3-cable connection
Pt100 resistance input current ~300 mA

Processing range (programmable)

- processing range minimum width	40°C
- factory setting	0 ÷ 100 °C
- measuring resolution	0,1 °C

Current output (programmable)

- load characteristics	R _{obc} < (Usup-10V) / 21mA < 1238 W
- output current resolutions	16000[mA] / (processing range[°C])
- maximum resolution	2mA
- nonlinearity	< 0,04%

Voltage output (programmable)

- load characteristics	I _{obc} < 4mA (R _{obc} > 2500 W)
- output voltage resolutions	10000[mV] / (processing range[°C])
- maximum resolution	1,25mV
- nonlinearity	< 0,04%

Processing basic error (25°C)

- for Pt100 input	< 0,2% of the full measuring range
- for thermocouple input	< 0,3% of the full measuring range
- processing resolution error (%)	±0,1°C x100 / processing range[°C]

Additional errors

- cold ends temperature compensation	< 2°C ((thermocouple inputs only))
- cables resistance compensation	< 0,1% Pt100 input measuring range
- environment temperature variation	< 0,01 % measuring range / °C

Rated operating environment

- supply (+Vz) - current output	10÷36Vdc (>10[V]+Robc[W]x0.021[A])
- supply (+Vz) - voltage output	18÷36Vdc, I _{obc} < 4mA
- operating temperature range	0 ÷ 65 °C
- operating relative humidity range	0 ÷ 90 %RH (non condensing)

Response time (10÷90%)

- programmable	in range 350÷1600 ms
- factory setting	900 ms

Indication of detected error

- optical	red LED
- current output signal	3,8 or 21 mA
- voltage output signal	10,6 V


Housing on TS35 rail

- dimensions	18 x 90 x 58 mm
- protection rating	IP40 (housing), IP20 (terminals)
- weight	~ 20g

Electromagnetic compatibility (EMC)


- immunity: acc. to PN-EN 61000-6-2	
- emission: acc. to PN-EN 61000-6-4	

DESCRIPTION OF THE TERMINAL BLOCK



HOUSING AND INSTALLATION

Dimensions 18 x 90 x 58 mm
Installation on TS35 rail
Material self-extinguishing material PPO
Connecting loads and supply screw terminals



HOW TO ORDER

AR580 / U ... 3-wire version with voltage output
AR580 / I ... 2-wire version with current output

Please specify in order:

AR580 / input / range / output / for thermocouples
way to compensate for temperature of cold ends

For example :

1. **AR580 / J / 100...500°C / 20...4mA / auto**
Thermocouple J type input, processing range 100 ÷ 500 °C, output 20 ÷ 4mA with automatic temperature compensation of cold ends
2. **AR580 / J / 100...500°C / 4...20mA / 25°C**
Thermocouple J type input, processing range 100 ÷ 500 °C, output 4 ÷ 20mA with constant cold temperature compensation of 25 °C
3. **AR580 / Pt100 / 0...500°C / 0...10V**
Pt100 input, processing range 0 ÷ 500 °C, 3-wire output 0 ÷ 10V